

PRODUCT NAME: COMPLIANCE

PRODUCT NUMBER: 431013

PAGE 1

MATERIAL SAFETY DATA SHEET

Per 29 CFR 1910.1200

DATE PREPARED : 8/20/93

SECTION I:

BRULIN & COMPANY, INC. P.O. BOX 270, INDIANAPOLIS, IN 46206-0270 (317) 923-3211

WEST COAST FACTORY
Richmond, California

SOUTHEASTERN FACTORY
Tampa, Florida

24 HOUR EMERGENCY NUMBER (317) 923-3233
CHEMTREC 1-800-424-9300

IDENTITY (As listed on label):
COMPLIANCE

Health: 1
HMIS HAZARD RATINGS: Flammability: 0
Reactivity: 0

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components (Specific Chemical Identity: Common Name(s))	CAS #	OSHA PEL	ACGIH TLV-TWA	OTHER LIMITS RECOMMENDED	PERCENT
Dipropylene glycol methyl ether	34590-94-8	100 PPM	100 PPM	STEL 150 PPM	1-5
2 Propanol, 1-methoxy; Propylene glycol methyl ether	107-98-2	100 PPM	100 PPM	STEL 150 PPM	1-5

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: 212 F
Vapor Pressure (mm Hg): Unknown
Vapor Density (Air = 1): Unknown
Solubility in Water: Complete
Appearance and Odor: Light yellow liquid, citrus odor

Specific Gravity (H₂O = 1): 1.054
Melting Point: Approx. 30 F
Evaporation Rate (= 1): 1.0

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): None
Flammable Limits LEL NA UEL NA
Extinguishing Media: NA
Special Fire Fighting Procedures: None
Unusual Fire and Explosion Hazards: None

SECTION V - REACTIVITY DATA

Stability Unstable Stable Conditions to Avoid: Freezing
 Incompatibility (Materials to Avoid): Strong acids
 Hazardous Decomposition or Byproducts: Carbon monoxide, upon thermal decomposition
 Hazardous Polymerization: May Occur May Not Occur
 Conditions to Avoid: None

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry: Ingestion? No Skin? Yes Inhalation? Yes Eyes?
 Health Hazards (Acute and Chronic): Direct eye contact may cause irritation. Excessive inhalation may cause nasal and respiratory irritation. Prolonged or repeated skin contact may cause irritation. Ingestion may cause gastrointestinal irritation.
 Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No
 Signs and Symptoms of Exposure: Eye irritation seen as redness, tearing. Excessive inhalation may cause drowsiness, light-headedness, weakness, headache. Skin irritation seen as slight redness.
 Medical Conditions Generally Aggravated by Exposure: None known
 Emergency & First Aid Procedures:
 Eye Contact: Flush with large quantities of water for 15 minutes lifting upper and lower lids occasionally.
 Inhalation: Remove to fresh air. Administer oxygen if breathing is difficult.
 Skin Contact: Wash with mild soap and water. Remove contaminated clothing and launder before reuse.
 Ingestion: If conscious, dilute by giving 2 glasses of water. Keep warm and quiet and call physician or local poison control center immediately.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: Absorb with solid absorbent and shovel into containers for disposal
 Waste Disposal Method: Dispose according to Federal, State and Local laws and 40 CFR.
 Precautions to be Taken in Handling and Storing: Store between 40 and 120 F

SECTION VIII - CONTROL MEASURES

Respiratory Protection (Specify Type): Not normally required, however, if the potential of overexposure exists, wear NIOSH approved respirator for organic vapors.
 Ventilation: Mechanical (General) ventilation is sufficient
 Protective Gloves: Recommended (rubber)
 Eye Protection: Recommended
 Other Protective Clothing or Equipment: As necessary to prevent skin contact.
 Work/Hygienic Practices: Avoid breathing spray mist. Wash hands after handling.