

# CLEANING LABORATORY EVALUATION SUMMARY

SCL #: 2021  
 DateRun: 07/21/2021  
 Experimenters: Ross Goding, Edward Judge  
 ClientType: Lab  
 ProjectNumber: Project #4  
 Substrates: Glass/Quartz, Other, Chrome  
 PartType: Coupon  
 Contaminants: Glass  
 Cleaning Methods: Manual Wipe  
 Analytical Methods: Gravimetric, Visual  
 Purpose: To test the effectiveness of Murphy Oil Soap in the removal of SSL Soil 2 Glass Soil from various substrates.

Experimental Procedure: A Murphy Oil Soap solution was created by mixing 3mL of Murphy Oil Soap with 192mL of water. Then, 3 coupons of each substrate (chrome, glass, mirror) were collected and initial weights were taken. SSL Soil 2 Glass Soil was applied to each coupon and allowed to air dry for 24 hours. After the 24 hour dry time, the weights of the newly contaminated coupons were measured. All coupons were placed into a Gardner-scrub Abrasion Tester machine. Wypall cleaning cloths were attached to each of the 3 cleaning blocks used for the test. Each Wypall cloth and all coupons received 2 sprays of the Murphy Oil Soap solution and the Gardner-scrub Abrasion Tester was run for 20 repetitions, simulating 20 manual wipes. Once cleaning concluded, the cleaned coupons were allowed to air dry for 24 hours. After 24 hours, the weights of the cleaned coupons were measured.

Results:	Cleaner	Substrate	Initial wt of cont.	Final wt of cont.	%Cont Removed	% AVG	% Overall
	Murphy Oil Soap	Chrome	0.0577	0.0015	97.40	86.05	85.42
			0.0864	0.0025	97.11		
			0.0840	0.0385	54.17		
		Glass	0.0782	0.0035	95.52	81.95	
			0.0823	0.0036	95.63		
			0.0806	0.0365	54.71		
		Mirror	0.0749	0.0021	97.20	88.27	
			0.0790	0.0014	98.23		
			0.0774	0.0237	69.38		

Summary:		<b>Substrates:</b> Glass/Quartz, Other, Chrome			
		<b>Contaminants:</b> Glass			
<b>Company Name:</b>	<b>Product Name:</b>	<b>Conc.:</b>	<b>Efficiency:</b>	<b>Effective:</b>	<b>Observations:</b>
Colgate-Palmolive Company	Murphy Oil Soap	1:64	85.42	<input checked="" type="checkbox"/>	Murphy Oil Soap was effective in the removal of Glass Soil from various substrates.

Conclusion: Murphy Oil Soap was successful in the removal of SSL Soil 2 Glass Soil from chrome, glass, and mirror substrates.